

Mills

- USOP: In machine measuring system (spindle) optical type touch sensor
- Mori Seiki Dura Vertical 5100 with Nikken CNCZ202 Indexer (40 Taper, Travels 41.3" x 20.9" x 20.1")
- Mori Seiki Dura Vertical 5100 with Nikken CNC200 Indexer (40 Taper, travels 41.3" x 20.9" x 20.1")
- Mori Seiki Dura Vertical 5100 with Nikken 10" Chuck (40 Taper, Travels 41.3" x 20.9" x 20.1")
- Mori Seiki Vertical 5100
- Okuma MX-45VAE Vertical Machining Center with Indexer (40 Taper, Travels 30" x 18" x 17")
- Bridgeport Milling Machine
- Nikken CNC 100-3W-120-A21 Three Spindle Rotary Table with Pneumatic Tail Stocks (3" Dia. X 24" Length)
- Horizontal Mill: DMG Mori NHX 4000

Lathes

- Okuma Twin Turret/Twin Spindle with Live Tooling & "Y" Axis (7.5" Dia. X 27.5" Length)
- Okuma LB25II Series CNC Lathe - 15" Chuck & 4" Big-Bore Spindle (17" Dia. X 20" Length)
- Okuma LB15II CNC Lathe - 8" Chuck (14" Dia. X 16" Length)
- Okuma LB35II CNC Lathe - 15" Chuck (19.25" Dia. X 36" Length)
- Okuma Crown – Big Bore Spindle & Bar Feed (14" Dia. x 16" Length)
- Okuma Crown – 8" Chuck (14" Dia. X 16" Length)
- Okuma Crown – 1-5/8" Cap Collet (14" Dia. x 16" Length)
- Hardinge Super Precision DSMFive Nine-R
- KIA SKT25 CNC Lathe – 10" Chuck (24.4" Dia. x 28.5" Length)
- DMG Mori NLX 1500 SY/500 – Twin Turret/Twin Spindle with Live Tooling & "Y" Axis